




CAPACITIES APPLY TO OPERATION ON FIRM LEVEL SURFACE					
LOAD RADIUS METERS	MAIN BOOM OR EXTENSION CAPACITIES IN KILOGRAMS				
	360° ROTATION		OVER FRONT		
	ON RUBBER	ON OUTRIGGERS	ON RUBBER	ON OUTRIGGERS	
<b>1.5</b>	<b>4260</b>	<b>7710</b>	<b>5170</b>	<b>8160</b>	
<b>2.0</b>	<b>3140</b>	<b>5790</b>	<b>4290</b>	<b>5790</b>	
<b>2.5</b>	<b>2470</b>	<b>4400</b>	<b>3580</b>	<b>4400</b>	
<b>3.0</b>	<b>1990</b>	<b>3560</b>	<b>2830</b>	<b>3560</b>	
<b>3.5</b>	<b>1560</b>	<b>2910</b>	<b>2180</b>	<b>2910</b>	
<b>4.0</b>	<b>1270</b>	<b>2520</b>	<b>1720</b>	<b>2520</b>	
<b>4.5</b>	<b>1060</b>	<b>2210</b>	<b>1400</b>	<b>2210</b>	
<b>5.0</b>	<b>890</b>	<b>1950</b>	<b>1170</b>	<b>1950</b>	
<b>5.5</b>	<b>740</b>	<b>1760</b>	<b>990</b>	<b>1760</b>	
<b>6.0</b>	<b>630</b>	<b>1570</b>	<b>840</b>	<b>1570</b>	
<b>6.5</b>	<b>540</b>	<b>1430</b>	<b>730</b>	<b>1430</b>	
<b>7.0</b>	<b>480</b>	<b>1330</b>	<b>650</b>	<b>1330</b>	
<b>7.5</b>	<b>430</b>	<b>1200</b>	<b>580</b>	<b>1230</b>	
<b>8.0</b>	<b>380</b>	<b>1090</b>	<b>530</b>	<b>1140</b>	
<b>8.5</b>	<b>340</b>	<b>1000</b>	<b>500</b>	<b>1070</b>	
<b>9.0</b>	<b>290</b>	<b>910</b>	<b>460</b>	<b>990</b>	
<b>10.0</b>	<b>180</b>	<b>760</b>	<b>390</b>	<b>850</b>	
<b>11.0</b>	<b>110</b>	<b>650</b>	<b>310</b>	<b>740</b>	
<b>12.2</b>	<b>60</b>	<b>520</b>	<b>220</b>	<b>630</b>	
3M BOOM EXT. BOOM EXTENSION	3-METER BOOM EXTENSION - STRAIGHT OR OFFSET				
	MAIN BOOM ANGLE				
	ANGLE	0°	30°	45°	60°
*† 0°	<b>1020</b>	<b>1180</b>	<b>1450</b>	<b>2260</b>	<b>3170</b>
† 15°	---	<b>1090</b>	<b>1220</b>	<b>1580</b>	<b>1900</b>
† 30°	---	<b>1020</b>	<b>1130</b>	<b>1360</b>	<b>1490</b>

\* USE 0° FOR STRAIGHT BOOM EXTENSION.  
† USE 0°, 15° OR 30° FOR OFFSET BOOM EXTENSION.


CAUTION BOOM EXTENSION LOADS MUST NOT EXCEED MAIN BOOM CAPACITY. DO NOT PICK & CARRY WITH LOADS ON BOOM EXTENSION.

CAPACITIES ON OUTRIGGERS ARE 85% OF TIPPING LOADS. CAPACITIES ON RUBBER ARE 75% OF TIPPING LOADS. CAPACITIES BELOW BOLD LINE ARE LIMITED BY TIPPING. OTHER CAPACITIES ARE LIMITED BY STRUCTURAL OR HYDRAULIC CAPABILITY.

BOOM EXTENSION DEDUCT: 45 KGS WHEN STOWED ON BASE BOOM.



USE SINGLE PART LOAD LINE FOR LOADS TO 4090 KGS. (WT. 40 KGS.)



USE TWO PART LOADLINE FOR LOADS TO 8180 KGS. (WT. 56 KGS.)

